

2 in 1 –  
Vertical and horizontal steam  
ironing system

Scratch-resistant „Superglide“  
ceramic soleplate with  
outstanding sliding behaviour

Quick warm-up time

Use for up to 20 min. on a full  
tank



Vertical steam ironing  
for hanging clothes



**Combined attachment:**  
Textile brush attachment for  
gentle and efficient  
method of removing  
wrinkles from fabrics and  
fluffs attachment for  
removing wrinkles and  
fluffs

without decoration



**NEW!** Steam brush  
DB 3717

- 2 in 1 – Vertical and horizontal steam ironing system
- Steam brush for steam ironing, smoothing and removing fluff
- Scratch-resistant „Superglide“ ceramic soleplate with outstanding sliding behaviour
- Combined attachment:
  - Textile brush attachment: Gentle and effective method for removing creases from fabrics
  - Fluff brush attachment: for smoothing and removing fluff
- The gentle steam effect extends the lifespan of your clothes
- Saves time over traditional ironing
- Also suitable for sensitive materials
- Quick warm-up time through high performance power – ready to use in around 30 seconds
- Water tank (detachable) with 200 ml capacity allows steam ironing for up to 6 clothing pieces at a time
- Use for up to 20 mins on a full tank
- Constant steam output: approx. 20 g/min.
- Ergonomic handle
- 7 steam nozzles for quick and gentle smoothing of fabrics
- Vertical steam ironing for hanging clothes, curtains etc.
- Extra large radius of action due to 1.8 m long connection cable
- On/off switch
- Indicator light
- Overheating protection
- Accessories: Textile brush attachment, fluff brush attachment
- 220–240 V, 50/60 Hz, 1100 W

Color: White/Blue  
Article no.: 263 891  
Article EAN-Code: 4 006 160 638 912  
Exportpack EAN-Code: 4 006 160 884 685  
PU: 4  
20"/40"/HQ Container: 3600 / 7200 / 8220

Dimensions (approx. W x H x D) and weight  
Unit: 110 x 270 x 100 mm; 850 g  
Box: 170 x 315 x 130 mm

Delivery: xxx

CTC Clatronic International GmbH  
Industriering Ost 40  
47906 Kempen  
Tel.: +49 (0) 21 52 / 20 06 0  
Fax: +49 (0) 21 52 / 20 06 19 99  
info@clatronic.de  
www.clatronic-germany.com