

Product Data Sheet

Model identifier	PC-HL 3116				
Item	Symbol	Value	Unit	Item	Unit
Heat output			Type of heat input, for electric storage local space heaters only		
Nominal heat output	P_{nom}	2.0	kW	manual heat charge control, with integrated thermostat	no
Minimum heat output (indicative)	P_{min}	1.0	kW	manual heat charge control with room and / or outdoor temperature feedback	no
Maximum continuous heat output	$P_{max,c}$	2.0	kW	electronic heat charge control with room and / or outdoor temperature feedback	no
Auxiliary electricity consumption			fan assisted heat output		
At nominal heat output	el_{max}	N.A.	kW	Type of heat output / room temperature control	
At minimum heat output	el_{min}	N.A.	kW	single stage heat output and no room temperature control	no
In standby mode	el_{sb}	0.0006	kW	Two or more manual stages, no room temperature control	no
			with mechanic thermostat room temperature control		
			with electronic room temperature control		
			electronic room temperature control plus day timer		
			electronic room temperature control plus week timer		
			Other control options		
			room temperature control, with presence detection		
			room temperature control, with open window detection		
			with distance control option		
			with adaptive start control		
			with working time limitation		
			with black bulb sensor		
Contact details	Clatronic International GmbH, Industriering Ost 40, 47906 Kempen, Germany				
N.A. = not applicable					