Product Data Sheet

Model identifier	PC-GKH 3118				
Item	Symbol	Value	Unit	Item	Unit
Heat output				Type of heat input, for electric storage local space heaters only	
Nominal heat output	P _{nom}	1,5	kW	manual heat charge control, with integrated thermostat	no
Minimum heat output (indicative)	P _{min}	0,75	kW	manual heat charge control with room and / or outdoor temperature feedback	no
Maximum continuous heat output	P _{max,c}	2,5	kW	electronic heat charge control with room and / or outdoor temperature feedback	no
Auxiliary electricity consumption				fan assisted heat output	no
At nominal heat output	el _{max}	0,000	kW	Type of heat output / room temperature control	
At minimum heat output	el _{min}	0,000	kW	single stage heat output and no room temperature control	no
In standby mode	elsa	0,00141	kW	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	yes
				with adaptive start control	no
				with working time limitation	yes
				with black bulb sensor	no
Contact details	Clatronic International GmbH, Industriering Ost 40, 47906 Kempen, Germany				